

In the Claims

1. (Currently Amended) A method comprising, with use of a processor:
~~for~~ downscaling a digital coloured matrix image by selected ratios M_2/M_1 and N_2/N_1 ,
 in which the matrix image includes N_1 rows, each row including M_1 pixels, so that the
 values of the pixels form the matrix and the pixels of different colours form the
 selected format, and
~~in which~~ using scaling is used to form an output matrix, of a size $M_2 \times N_2$, the pixels
corresponding to sub-groups of the original matrix, in such a way that $M_2 \leq M_1$ and
 $N_2 \leq N_1$, and from the values $\text{Input}(j,i)$ of which pixels (i,j) the value $\text{Output}(l,k)$ of
each output pixel (k,l) of the output matrix is calculated, characterized in that the
coloured matrix image is read only once and
forming the weighted sums of the values of the same-colour pixels (i,j) of the matrix
image in the area of each output pixel (k,l) is formed parallel in line memories
 $\{\text{Buffer}[0], \text{Buffer}[1]\}$ arranged for each colour,
calculating for each input pixel a the-weighting coefficient being representing the
dimension share of the pixel (i,j) in the area of the output pixel (k,l) , and
correcting each weighted sum is corrected by a scaling factor $(f \times M_2/M_1 \times N_2/N_1)$.

2. (Currently Amended) A method according to Claim 1, ~~characterized in that~~
wherein the scaling is carried out in one dimension (~~x~~) at a time, by calculating the
 intermediate sums $\text{Outx}(l)$ of this dimension in the a memory location ~~$\{\text{Data}[0],$~~
 ~~$\text{Data}[1]\}$~~ by forming the weighted sum of the intensities of the pixels of this
 dimension, the weighting coefficients being the proportion of each source pixel (i,j) in
 this dimension's output pixels (k,l) and by transferring the sum finally to the line
 memory ~~$\{\text{Buffer}[0], \text{Buffer}[1]\}$~~ , to each elementary unit (l) of which the intermediate
 sums $\text{Outx}(l)$ of the output pixel (k,l) of the corresponding column (k) are calculated.

3. (Currently Amended) A method according to Claim 2, ~~characterized in that~~
wherein the calculation is performed by using alternating pairs of memory locations
 ~~$\{\text{Data}[0], \text{Data}[1]\}$~~ and alternating pairs of line memory ~~$\{\text{Buffer}[0], \text{Buffer}[1]\}$~~ , in such a
 way that

- in the case of a part pixel (i,j), the initial part intensity of the following output pixel (k+1,l) is also always calculated to a second memory location, in which the summed intensity of the subsequent index (k+1) is in turn collected, and
- in the case of a part row, the intensity value of each pixel (i,j) is divided between both memory locations, in proportion to how the pixel covers the output pixel (k, l) and the following output pixel (k, l+1) in the corresponding dimension and is summed over the length of the output pixel and each first sum is stored in the next row buffer in turn and the second sum is stored in the second row buffer ((l+1)mod2), in which the sums of the following output row (l+1) are begun to be collected.

4. (Currently Amended) A method according to Claim 1, ~~characterized in that~~ wherein the output image is moved relative to the input image, in such a way that part of the information of the edge pixels of the input image is left unused and correspondingly, at the opposite edge, additional information is extrapolated to the input pixels.

5. (Currently Amended) An apparatus for downscaling a digital coloured matrix image by selected ratios ~~(M_2/M_1 and N_2/N_1)~~, which the apparatus includes an application memory for storing and processing the scaled matrix image, a central processing unit ~~(CPU)~~, a program memory area and a program stored into for performing the processing, and in which the matrix image includes N_1 rows, each row including M_1 pixels, so that the values of the pixels form the matrix and the pixels of different colours form the format, and in which the pixels of the output matrix, of a size $M_2 \times N_2$, formed by the scaling, correspond to sub-groups of the original matrix, from the values of which pixels the mean value of each pixel of the output matrix is calculated by calculating the sum of the values and dividing it by the scaling factor ~~($M_2/M_1 \times N_2/N_1$)~~, ~~characterized in that~~ wherein the apparatus is ~~arranged~~ configured ~~to read the coloured matrix image only once and to process the input pixels (k,l) individually, in such a way that the said sum of the values is formed parallel in line memories (Buffer[0], Buffer[1]) arranged for each colour weighted from the values of the same-colour matrix-image pixels (i,j) in the area of each output pixel (k,l), the~~

weighting coefficient being the dimension proportion of the pixel (i,j) in the area of the output pixel (k,l).

6. (Currently Amended) An apparatus according to Claim 5, ~~characterized in that~~ wherein the memory area includes four memory locations ~~(Data[0/1][0/1])~~ for each colour and two line memories ~~(Buffer[0], Buffer[1])~~ for each colour and that the apparatus is arranged to perform scaling in one dimension (~~x~~) at a time, by calculating the intermediate sums $\text{Outx}(l)$ of this dimension into a memory location ~~(Data[0], Data[1])~~ by forming the weighted sum of the intensities of the pixels of this dimension, the weighting factors being the proportion of each source pixel (i,j) in the output pixels (k,l) of this dimension and to transfer the sum finally to the line memory ~~(Buffer[0], Buffer[1])~~, the intermediate sums Outx corresponding to one calculated output pixel row (l) being arranged in each elementary unit (k).

7. (Currently Amended) An apparatus according to Claim 6, ~~characterized in that~~ wherein it includes an alternating pair of memory locations ~~(Data[0], Data[1])~~ and an alternating pair of line memories ~~(Buffer[0], Buffer[1])~~, to which address means are linked, which are arranged using the least significant bit of the functioning binary-form index (k, l), in such a way that

- in the case of a part pixel (i,j), the initial part intensity of the following output pixel (k+1,l) is also always calculated into a second memory location, in which the sum intensity of the following index (k+1) is in turn collected, and
- in the case of a part row, the intensity value of each pixel (i,j) is divided between both memory locations, in proportion to how the pixel covers the output pixel (k, l) and the following output pixel (k, l+1) in the corresponding dimension, and the part values are summed and stored over the length of the output pixel in the line memories ~~(Buffer[0], Buffer[1])~~.

8. (Currently Amended) An apparatus according to Claim 5, ~~characterized in that~~ wherein the apparatus is integrated in connection with the camera sensor of the camera.

9. (Currently Amended) An apparatus according to Claim 8 and including a host system, ~~characterized in that~~ wherein scaling in one dimension is integrated in connection with the camera sensor of the camera and the scaling in the other dimension with the host system.

10. (Currently Amended) An apparatus according to Claim 6, ~~characterized in that~~ wherein the apparatus includes a scaler component, in which there are separate processors ~~(CPU)~~ for scaling in each dimension.

11. (Currently Amended) An apparatus according to Claim 5, ~~characterized in that~~ wherein the apparatus includes memory for the scaling operations of at least two output-image lines for each colour component.

12. (Currently Amended) An apparatus according to Claim 5, ~~characterized in that~~ wherein the memory required in scaling is implemented in the processor ~~(CPU)~~.

13. (Currently Amended) An apparatus according to Claim 5, ~~characterized in that~~ wherein the apparatus is arranged in a mobile terminal.

14. (Currently Amended) A method comprising, with use of a processor: for downscaling a digital matrix image, by means of software, by selected ratios M_2/M_1 and N_2/N_1 , in a digital device, in which there is a scaling component including at least an input unit for bringing the input rows to the scaling component, a processor and memory for processing the data, and an output part from forwarding the processed data, and in which the matrix image includes N_1 rows, each row including M_1 pixels, so that the values of the pixels form the matrix and the pixels of different colours form the selected format, and in which the pixels of the output matrix, of a size $M_2 \times N_2$, formed by scaling, correspond to the sub-groups of the original matrix, in such way that $M_2 < M_1$ and $N_2 < N_1$, and from the values Input (j,i) of which pixels (i,j) the value Output (l,k) is calculated for each output pixel (k,l) of the output matrix, ~~characterized in that~~ wherein

- the coloured matrix image is read only once so that each input row is brought in turn, and each pixel is taken individually to the processor for processing,
- the weighting coefficient for each pixel is calculated in the area of the output pixel, the weighting coefficient depicting the part of the surface area of the pixel in the output pixel,
- the values of the pixels of the input row are summed in the area of each output pixel (k,l) according to a predefined sequence, in such a way that a weighted sum is formed parallel in line memories (~~Buffer[0], Buffer[1]~~) arranged for each colour and each sum is formed of the values of the same-colour matrix-image pixels (i,j) in the area of each output pixel (k,l), and each weighted sum is corrected by a scaling factor (~~$M_2/M_1 \times N_2/N_1$~~),
- the corrected sum is transferred out through the output part.

15. (Currently Amended) A method according to Claim 14, ~~characterized in that~~ wherein the memory includes at least two pairs of memory locations (~~Data[0], Data[1]~~) for summing the intensities and two line memories (~~Buffer[0], Buffer[1]~~), and in which

- the relationship of the input line j to the output line l is defined and
- the intermediate sums $\text{Outx}(i,l)$ in the selected dimension (~~x~~) are calculated to the memory location $\text{Data}[k \bmod 2]$ that is now in turn and the final part of the part pixel to the second memory location ($\text{Data}[(k+1) \bmod 2]$) and the sum is finally transferred to the line memory (~~Buffer[0], Buffer[1]~~), to each elementary unit (l) of which the intermediate sums $\text{Outx}(i,l)$ of the output pixel (k,l) of the corresponding column (l) are calculated.

16. (Currently Amended) A method according to Claim 15, ~~characterized in that~~ wherein

- the memory locations (~~Data[0], Data[1]~~) of the pair of memory locations and the line memories (~~Buffer[0], Buffer[1]~~) of the pair of line memories are addressed with the aid of an alternating function,

- in the case of a part pixel (i,j) the initial part intensity of the following output pixel $(k+1,l)$ is always also calculated and is stored in the second memory location, in which the sum intensity of the index $(k+1)$ following in turn is collected, and
- in the case of a part row, the intensity value of each pixel (i,j) is divided and stored in both memory locations in proportion to how the pixel and the following pixel $(k,l+1)$ cover the output pixel (k,l) in the corresponding dimension (y) , and are summed over the length of the output pixel and the first sum of each is stored in the line memory now in turn and the second sum in the second line memory $((l+1)\bmod 2)$, in which the sums of the following output row $(l+1)$ are begun to be collected.

17. (New) An apparatus comprising:

means configured to downscale a digital coloured matrix image by selected ratios $(M_2/M_1 \text{ and } N_2/N_1)$ to form an output matrix, said digital coloured matrix image including N_1 rows, each row including M_1 pixels, so that the values of the pixels form the digital coloured matrix and the pixels of different colours form the format, and the pixels of the output matrix, of a size $M_2 \times N_2$, formed by the scaling, correspond to sub-groups of the digital coloured matrix,

means configured to communicate with an application memory for storing and processing the scaled matrix image,

means configured to calculate the mean value of each pixel of the output matrix from the values of pixels by calculating the sum of the values and dividing the sum by a scaling factor,

wherein the apparatus is configured to process the input pixels (k,l) individually, in such a way that the said sum of the values is formed parallel in line memories arranged for each colour weighted from the values of the same-colour matrix-image pixels (i,j) in the area of each output pixel (k,l) , the weighting coefficient being the dimension proportion of the pixel (i,j) in the area of the output pixel (k,l) .

18. (New) A method according to Claim 1, comprising:

forming said weighted sums by using an alternating pair of line memories arranged for each colour, each line memory having the width of an output image.

19. (New) An apparatus according to Claim 5, wherein said sum of the values is formed by using an alternating pair of line memories arranged for each colour, each line memory having the width of an output image.

20. (New) An apparatus according to Claim 17, wherein said sum of the values is formed by using an alternating pair of line memories arranged for each colour, each line memory having the width of an output image.